



• ***Export Field Descriptions*** •

Version: 10.9.0.0

Power through High-Stakes E-Discovery with
One Platform

Table of Contents

1	VenioOne Field Description	2
2	New Field – Log	14
3	Renamed Field – Log	18
4	Removed Field – Log	19

1 VenioOne Field Description

Field Group	Field Name	Description	Data Type	Remark
COMMON	ATTACHMENT_CONTROL_NUMBER_RANGE	Populated with CONTROL_NUMBER of 1st & the last attachment in the family set separated by '-'. (If there are no attachment then this field will empty.)	TEXT	
COMMON	ATTACHMENT_CONTROL_NUMBERS	Populated with "CONTROL_NUMBER" of children document for its parent (for child document its empty).	TEXT	This field is populated both for parent Email and Edoc document.
COMMON	ATTACHMENT_COUNT	Populated with number of children document in a family. This field is populated only on parent document. For child documents it is empty.	NUMERIC	This field is populated both for parent Email and Edoc document. If an email has an attachment (e.g word file) and this word file has another embedded text file. Then, this emails child could would be 2.
COMMON	ATTACHMENT_COUNT_PRODUCED	Populated with number of child documents of a family in export. Populated only for parent document.	NUMERIC	
COMMON	ATTACHMENT_FILE_NAMES	Populated from "FILE_NAMES" field of all children document in a family. This field is populated only on parent document. For child document it is empty. (default delimiter=;)	MULTI VALUED	This field is populated both for parent Email and Edoc document.
COMMON	ATTACHMENT_FILE_NAMES_PRODUCED	Populated with "FILE_NAMES" field of all child documents of a family in export. Populated only for parent document.	MULTI VALUED	
COMMON	BEGIN_ATTACHMENT_CONTROL_NUMBER	For parent documents, This field is populated with the "CONTROL_NUMBER" of 1st attachment in its family set.(If there are no attachment or if this document is not the parent, then this field will empty.)	TEXT	
COMMON	BEGIN_ATTACHMENT_CONTROL_NUMBER_ALL	Populated with the "CONTROL_NUMBER" of 1st attachment in its family set. (If there are no attachment, then this field will be empty.)	TEXT	
COMMON	BEGIN_CONTROL_NUMBER	Unique sequential value generated for each document based on prefix, padding & start number provided in export setting (per project).	TEXT	
COMMON	BEGIN_FAMILY_CONTROL_NUMBER	For parent documents,This field is populated with the "CONTROL_NUMBER" of its parent in its family set.(If this document is not the parent, then this field will be empty.)	TEXT	
COMMON	BEGIN_FAMILY_CONTROL_NUMBER_ALL	Populated with the "CONTROL_NUMBER" of parent in its family set.	TEXT	
COMMON	CONTROL_NUMBER	Unique sequential value generated for each document based on prefix, padding & start number provided in export setting	TEXT	

		(per project).		
COMMON	CUSTODIAN_ID	Venio's internal unique identifier for each custodian	NUMERIC	
COMMON	CUSTODIAN_NAME	Populated with custodian name assigned during project setup.	TEXT	
COMMON	DETECTED_ITEM_COUNT	Populated with number of embedded items or attachments present in this document.	NUMERIC	This field is populated for both parent and child documents with items embedded or attached. This field will also be populated for archive files if archive files are exported.
COMMON	DETECTED_LANGUAGE	Populated with identified language of the document.	TEXT	
COMMON	DETECTED_LANGUAGE_ALL	Populated with all identified language of the document.	TEXT	
COMMON	DOCUMENT_TYPE	Populated with identified document type.	TEXT	
COMMON	DUPLICATE_CUSTODIAN_NAMES	Populated with all custodian names which contain duplicates of this document. Applicable for only parent documents. For children documents, it will be empty.(default delimiter=;)	MULTI VALUED	
COMMON	DUPLICATE_CUSTODIAN_NAMES_ALL	Populated with all custodian names for all document in family which contain duplicates of this document.?(default delimiter=;)	MULTI VALUED	
COMMON	EMAIL_FOLDER_STRUCTURE	Populated with email folder structure within email container.	TEXT	This is populated for parent emails and its child documents within email archives. e.g. JohnDoe.pst\Inbox
COMMON	END_ATTACHMENT_CONTROL_NUMBER	For parent documents, This field is populated with the "CONTROL_NUMBER" of last attachment in its family set.(If there are no attachment or if this document is not the parent, then this field will empty.)	TEXT	
COMMON	END_ATTACHMENT_CONTROL_NUMBER_ALL	Populated with the "CONTROL_NUMBER" of last attachment in its family set. (If there are no attachment or if this document is not the parent, then this field will be empty.)	TEXT	
COMMON	END_CONTROL_NUMBER	Unique sequential value generated for each document based on prefix, padding & start number provided in export setting (per project).	TEXT	
COMMON	END_FAMILY_CONTROL_NUMBER	For parent documents, This field is populated with the "CONTROL_NUMBER" of last attachment in its family set.(If there are no attachment, then it will be populated with parent "CONTROL_NUMBER".If this documents is not the parent, then this field will be empty.)	TEXT	

COMMON	END_FAMILY_CONTROL_NUMBER_ALL	Populated with the "CONTROL_NUMBER" of last attachment in its family set.(If there are no attachment, the this field will be populated with parent "CONTROL_NUMBERS".)	TEXT	
COMMON	EXPORT_FULLTEXT_TYPE	Populated with fields "Extracted Text" or "TIFF OCR Text" or "Redacted OCR Text" or "Placeholder Text" based on the fulltext priority	TEXT	
COMMON	FAMILY_CONTROL_NUMBER	Populated with "CONTROL_NUMBER" of parent document for its family.	TEXT	If Parent Document is not produced, it will be populated with it's own 'Control Number'.
COMMON	FAMILY_CONTROL_NUMBER_RANGE	Populated with "CONTROL_NUMBER" of parent & the last attachment in the family set separated by '-'. (If there no attachment then this field will be populated with parent "CONTROL_NUMBER".)	TEXT	
COMMON	FAMILY_DATE	Populated with date from "FAMILY_DATE_TIME" field	DATE	
COMMON	FAMILY_DATE_TIME	Populated with the date and time from the parent document using first available date and time from Remark Column. "FAMILY_DATE_TIME" is propagated to its children.	DATE/TIME	<p>The sequence of date picked for the 'FAMILY_DATE_TIME' is as follows:</p> <p>Group Date Value for Edocs</p> <ol style="list-style-type: none"> 1. 'EDOC_LAST_MODIFIED_DATE_TIME' (metadata) 2. 'EDOC_CREATED_DATE_TIME' (metadata) 3. 'SYSTEM_LAST_MODIFIED_DATE_TIME' (file system) <p>Group Date Value for Emails</p> <ol style="list-style-type: none"> 1. 'EMAIL_START_DATE_TIME' (metadata) 2. 'EMAIL_END_DATETIME' (metadata) 3. 'EMAIL_SENT_DATE_TIME' (metadata) 4. 'EMAIL_RECEIVED_DATE_TIME' (metadata) 5. Email Last Modified Date (metadata) 6. Email Created Date (metadata) 7. 'SYSTEM_LAST_MODIFIED_DATE_TIME' (file system) <p>Note: 'EMAIL_START_DATE_TIME' and 'EMAIL_END_DATETIME' will not be used if it is not</p>

				selected during project setup.
COMMON	FAMILY_DOCUMENT_TYPE	Parent email and its child = "EMAIL" Parent edocs and its child = "EDOC"	TEXT	
COMMON	FAMILY_HASH_VALUE	Populated with combined "HASH_VALUE" of the parent and this document.	TEXT	For parent: [Hashvalue of this document][Hashvalue of this document] For child : [Hashvalue of its parent][Hashvalue of this document]
COMMON	FAMILY_INTERNAL_FILE_ID	Document grouped together based on Venio's INTERNAL_FILE_ID. All documents within same family have same "FAMILY_INTERNAL_FILE_ID" value.	NUMERIC	For parent document, 'FAMILY_INTERNAL_FILE_ID' is same as its 'INTERNAL_FILE_ID'.For children documents, 'FAMILY_INTERNAL_FILE_ID' is same as it's parent's 'INTERNAL_FILE_ID'.
COMMON	FAMILY_TIME	Populated with time from "FAMILY_DATE_TIME" field	TIME	
COMMON	FILE_FORMAT_GROUP	Populated with identified file format group. Please see next column Remake for groups.	TEXT	Possible file type groups are : 1. Word Processor 2. Database 3. Spreadsheet 4. Graphic 5. Other 6. Multimedia 7. Special 8. Unknown Application 9. XML 10. Reserved 11. OEM 12. Bitmap 13. Email 14. Presentation 15. Archive 16. Email Archive 17. HTML 18. JPG 19. Microsoft Excel 20. Microsoft OneNote 21. Microsoft Powerpoint 22. Microsoft Project 23. Microsoft Word 24. Microsoft Access 25. PDF 26. RTF 27. System Files 28. Text 29. TIFF
COMMON	FILE_PASSWORD	File Password	TEXT	
COMMON	FILE_SIZE	Populated with calculated file size of the document.	NUMERIC	File size calculated in bytes.
COMMON	HAS_HIDDEN_OBJECT	Populated with YES/NO whether document has hidden objects.	BINARY	Hidden object implies a document has any of the following hidden objects , hidden text, hidden cell, hidden

				row/column, hidden sheet, track changes (added/deleted), slide hidden. YES/NO can be changed to other format from export setting (E.g. T/F, 1/0)
COMMON	GROUP_HASH_VALUE	Populated using hash value of all the documents in the family set	TEXT	
COMMON	HASH_VALUE	Populated with hash value of the document.	TEXT	
COMMON	HASH_VALUE_SECONDARY	Populated with secondary hash value. Eg. If MD5 is primary then SHA1 is secondary	TEXT	
COMMON	IMMEDIATE_SOURCE_INTERNAL_FILE_ID	Populated with Venio's internal unique identifier of the immediate source where the file was extracted from. For files in the root level, this field will be empty.	NUMERIC	For parent: [Hashvalue of this document][Hashvalue of this document] For child : [Hashvalue of its parent][Hashvalue of this document]
COMMON	INTERNAL_FILE_ID	Venio's internal unique identifier for each document per project.	NUMERIC	
COMMON	IS_CHILD	Populated YES/NO if document is identified as child and empty if document is archive	BINARY	
COMMON	IS_CORRUPTED_FILE	Populated YES/NO if document is identified as corrupted document.	BINARY	
COMMON	IS_CUSTODIAN_LEVEL_DUPLICATE	Populated with YES/NO whether document is custodian level duplicate file.	BINARY	
COMMON	IS_DECRYPTED_FILE	Is Decrypted File	BINARY	
COMMON	IS_DENISTED_FILE	Populated with YES/NO if the document is identified in the denist list.	BINARY	
COMMON	IS_EDOC_EMBEDDED_FILE	Populated YES/NO If document is an embedded object.	BINARY	
COMMON	IS_EMAIL_ATTACHMENT	Populated YES/NO whether document is an attachment.	BINARY	
COMMON	IS_EXCEPTION_FILE	Populated with YES/NO if document is identified as exception file.	BINARY	Exception file are those identify as issue that is outside of Venio control such as 'IO Error', 'System Error', 'Memory Error', 'Network Error', 'Database Error'
COMMON	IS_NO_TEXT_FILE	Populated with YES/NO if document is identified as not having any text.	BINARY	
COMMON	IS_PARENT	Populated with YES/NO whether document is a parent document.	BINARY	
COMMON	IS_PASSWORD_PROTECTED_FILE	Populated with YES/NO if the document is identified as password protected file.	BINARY	
COMMON	IS_PROJECT_LEVEL_DUPLICATE	Populated with YES/NO whether document is project level duplicate file.	BINARY	
COMMON	IS_SYSTEM_FILE	Populated with YES/NO if the document is identified as system file.	BINARY	

COMMON	IS_WRITE_PROTECTED	Populated with YES/NO if the document is identified as write protected.	BINARY	
COMMON	MASTER_DATE	Populated with Date from "MASTER_DATE_TIME" field	DATE	
COMMON	MASTER_DATE_TIME	Each document is populated with it own date and time. "FAMILY_DATE_TIME" for parent document and child documents is populated with it's squence based on Remark column.)	DATE/TIME	<p>The sequence of date picked for the child document value is as follows:</p> <p>'MASTER_DATE' value for child Edocs</p> <ol style="list-style-type: none"> 'EDOC_LAST_MODIFIED_DATE_TIME' (metadata) 'EDOC_CREATED_DATE_TIME' (metadata) 'SYSTEM_LAST_MODIFIED_DATE_TIME' (file system) <p>'MASTER_DATE' Value for child Emails</p> <ol style="list-style-type: none"> 'EMAIL_START_DATE_TIME' (metadata) 'EMAIL_END_DATETIME' (metadata) 'EMAIL_SENT_DATE_TIME' (metadata) 'EMAIL_RECEIVED_DATE_TIME' (metadata) Email Last Modified Date (metadata) Email Created Date (metadata) 'SYSTEM_LAST_MODIFIED_DATE_TIME' (file system) <p>Note: 'EMAIL_START_DATE_TIME' and 'EMAIL_END_DATETIME' will not be used if it is not selected during project setup.</p>
COMMON	MASTER_TIME	Populated with time from "MASTER_DATE_TIME" field	TIME	
COMMON	MEDIA_ID	Venio's internal unique identifier for each media	NUMERIC	
COMMON	MEDIA_NAME	Populated with media name assigned during project setup.	TEXT	
COMMON	MEDIA_NOTE	Populated with notes added to the media assigned during project setup.	TEXT	
COMMON	ORIGINAL_FAMILY_INTERNAL_FILE_ID	Populated with "FAMILY_INTERNAL_FILE_ID" of its original family document for project level duplicate. For original documents it will be	NUMERIC	

		empty.		
COMMON	ORIGINAL_FILE_EXTENSION	Populated with file extension extracted from file name.	TEXT	
COMMON	ORIGINAL_FILE_FOLDER_PATH	Populated with full file path excluding filename. (Child document inherits "ORIGINAL_FILE_FOLDER_PATH" from its parent)	TEXT	e.g. D:\Test Files\Basic Test Documents\Archive\JohnDoe.pst\Inbox
COMMON	ORIGINAL_FILE_NAME	Populated with the name of document.	TEXT	
COMMON	ORIGINAL_FILE_PATH	Populated with original full file path of the document.	TEXT	e.g. D:\Test Files\Basic Test Documents\Archive\JohnDoe.pst\Inbox\sample.msg
COMMON	PARENT_CONTROL_NUMBER	Populated with "CONTROL_NUMBER" of parent document for children documents (for parent document it is empty).	TEXT	If Parent Document is not produced, the field will be empty.
COMMON	RECOGNIZED_FILE_EXTENSION	Populated with file extension that is detected by file header analysis and associated with mapped file extensions.	TEXT	Venio maintains a database of file format & its associated file extension. If a file's 'ORIGINAL_FILE_EXTENSION' does not exist for given file format in Venio database, this field will be populated with default extension in database for the given file format.'
COMMON	RECOGNIZED_FILE_FORMAT	Populated with identified file format using file header analysis.	TEXT	e.g. POWERPOINT97,EXCEL2003,WINWORD2003,OUTLOOK_MSG,EXCEL2000,PDF,WINWORD2003
COMMON	RELATIVE_FILE_FOLDER_PATH	Populated with relative file path excluding document name. (Child document inherits "RELATIVE_FILE_FOLDER_PATH" from its parent)	TEXT	e.g. \Archive\JohnDoe.pst\Inbox
COMMON	SYSTEM_CREATED_DATE	Populated with date from "SYSTEM_CREATED_DATE_TIME" field.	DATE	
COMMON	SYSTEM_CREATED_DATE_TIME	Populated with created date/time identified from properties of a Operating System.	DATE/TIME	
COMMON	SYSTEM_CREATED_TIME	Populated with time from "SYSTEM_CREATED_DATE_TIME" field.	TIME	
COMMON	SYSTEM_LAST_ACCESS_DATE	Populated with date from "SYSTEM_LAST_ACCESS_DATE_TIME" field.	DATE	
COMMON	SYSTEM_LAST_ACCESS_DATE_TIME	Populated with last access date/time identified from properties of a Operating System.	DATE/TIME	
COMMON	SYSTEM_LAST_ACCESS_TIME	Populated with time from "SYSTEM_LAST_ACCESS_DATE_TIME" field.	TIME	
COMMON	SYSTEM_LAST_MODIFIED_DATE	Populated with date from "SYSTEM_LAST_MODIFIED_DATE_TIME" field.	DATE	

		E" field		
COMMON	SYSTEM_LAST_MODIFIED_DATE_TIME	Populated with modified date/time identified from properties of a Operating System.	DATE/TIME	
COMMON	SYSTEM_LAST_MODIFIED_TIME	Populated with time from "SYSTEM_LAST_MODIFIED_DATE_TIME" field	TIME	
COMMON	TIMEZONE	Timezone selected for ingestion.	TEXT	
COMMON	TIMEZONE_OFFSET	Offset of selected timezone during ingestion.	DECIMAL	
COMMON	TIMEZONE_WINDOWS_FORMAT	Time zone in windows display format	TEXT	
COMMON	DUPLICATE_FILE_PATH	Populated with relative file path of all duplicates of this document. Applicable for only parent documents. For children documents, it will be empty.(default delimiter=;)	TEXT	6.5.0.23
COMMON	DUPLICATE_FILE_PATH_ALL	Populated with relative file path of all duplicates of parent file for all document in family(default delimiter=;)	TEXT	6.5.0.23
EMAIL	EMAIL_ATTACHMENTS	Populated with file names of email attachments.	MULTI VALUED	
EMAIL	EMAIL_BCC	Populated with Email Receptient "BCC"	MULTI VALUED	
EMAIL	EMAIL_CATEGORY	Populated with email metadata "category"	MULTI VALUED	
EMAIL	EMAIL_CC	Populated with Email Receptient "CC"	MULTI VALUED	
EMAIL	EMAIL_CLIENT	Populated with identified known email client.	TEXT	For all Outlook message files, contact, appointment, journal, task : MS Outlook For MIMEOUTLOOKEML : Outlook express For DXL_MAILMESSAGE : Lotus notes Otherwise : Unknown
EMAIL	EMAIL_CONTAINER_NAME	Populated with file name of email container from which it was extracted. For loose emails, it will have filename of loose email.	TEXT	
EMAIL	EMAIL_CONVERSATION_ID	Populated with email metadata "ConversationId"	TEXT	
EMAIL	EMAIL_CREATED_DATE	Populated with date from "EMAIL_CREATED_DATE_TIME" field	DATE	
EMAIL	EMAIL_CREATED_DATE_TIME	Populated with email metadata "email created date/time"	DATE/TIME	
EMAIL	EMAIL_CREATED_TIME	Populated with time from "EMAIL_CREATED_DATE_TIME" field	TIME	
EMAIL	EMAIL_CUSTOM_BASE_INDEX	Populated with first 44 characters of CUSTOMCONVERSATIONID field	TEXT	

EMAIL	EMAIL_CUSTOM_CONVERSATION_INDEX	Populted with custom conversationid generated by venio to show email thread	TEXT	
EMAIL	EMAIL_DELIVERY_RECEIPT_REQUESTED	Populated YES/NO if email delivery receipt was requested.	BINARY	
EMAIL	EMAIL_DOMAIN_NAMES	Populated with domain names of sender and receiptents	TEXT	
EMAIL	EMAIL_END_DATE	Populated with date from "EMAIL_END_DATE_TIME" field	DATE	
EMAIL	EMAIL_END_DATE_TIME	Populated with calender entry ending date and time	DATE/TIME	
EMAIL	EMAIL_END_TIME	Populated with time from "EMAIL_END_DATE_TIME" field	TIME	
EMAIL	EMAIL_ENTRYID	Populated with email metadata "EntryId"	TEXT	
EMAIL	EMAIL_FROM	Populated with email sender	MULTI VALUED	
EMAIL	EMAIL_HAS_ON_BEHALF_OF_ADDRESS	Populated with YES/NO if email was send on behalf of another address.	BINARY	
EMAIL	EMAIL_IMPORTANCE	Populated with email metadata "Importance"	TEXT	
EMAIL	EMAIL_IN_REPLY_TO	Populated with "InReplyTo" from email header	MULTI VALUED	
EMAIL	EMAIL_INTERNET_MESSAGE_HEADER	Populated with the list of technical details about the message, such as who sent it, the software used to compose it, and the email servers that it passed through on its way to the recipient	TEXT	
EMAIL	EMAIL_IS_UNREAD	Populated with YES/NO if document is read or not	BINARY	
EMAIL	EMAIL_MESSAGE_CLASS	Populated with email message class from email metadata.	TEXT	e.g IPM.note, IPM.Contact etc
EMAIL	EMAIL_MESSAGE_ID	Populated with email metadata "MessageId"	TEXT	
EMAIL	EMAIL_MODIFIED_DATE	Populated with date from "EMAIL_MODIFIED_DATE_TIME" field	DATE	
EMAIL	EMAIL_MODIFIED_DATE_TIME	Populated with email metadata "email modified date/time"	DATE/TIME	
EMAIL	EMAIL_MODIFIED_TIME	Populated with time from "EMAIL_MODIFIED_DATE_TIME" field	TIME	
EMAIL	EMAIL_NORMALIZED_SUBJECT	Populated with normalized email subject MAPI.	TEXT	
EMAIL	EMAIL_NSF_UNIVERSAL_ID	Populated with Lotus Notes universal identifier.	TEXT	
EMAIL	EMAIL_ON_BEHALF_OF_ADDRESS	Populated with email address that was sent by who it claims to be from	TEXT	
EMAIL	EMAIL_READ_RECEIPT_REQUESTED	Populated YES/NO if email read receipt was requested.	BINARY	
EMAIL	EMAIL_RECEIVED_DATE	Populated with date from "EMAIL_RECEIVED_DATE_TIME" field	DATE	

EMAIL	EMAIL_RECEIVED_DATE_TIME	Populated with email metadata "email received date/time"	DATE/TIME	
EMAIL	EMAIL_RECEIVED_TIME	Populated with time from "EMAIL_RECEIVED_DATE_TIME" field	TIME	
EMAIL	EMAIL_RECIPIENTS	Concatenated fields of email To,CC,BCC. Delimter used is ;	MULTI VALUED	
EMAIL	EMAIL_REFERENCES	Populated with "References" from email header	MULTI VALUED	
EMAIL	EMAIL_SENSITIVITY	Populated with email metadata "sensitivity"	TEXT	
EMAIL	EMAIL_SENT_DATE	Populated with date from "EMAIL_SENT_DATE_TIME" field	DATE	
EMAIL	EMAIL_SENT_DATE_TIME	Populated with email metadata "email sent date/time"	DATE/TIME	
EMAIL	EMAIL_SENT_TIME	Populated with time from "EMAIL_SENT_DATE_TIME" field	TIME	
EMAIL	EMAIL_START_DATE	Populated with date from "EMAIL_START_DATE_TIME" field	DATE	
EMAIL	EMAIL_START_DATE_TIME	Populated with calender entry starting date and time	DATE/TIME	
EMAIL	EMAIL_START_TIME	Populated with time from "EMAIL_START_DATE_TIME" field	TIME	
EMAIL	EMAIL_SUBJECT	Populated with email subject	TEXT	
EMAIL	EMAIL_TO	Populated with Email Receptient "TO"	MULTI VALUED	
EMAIL	IS_INCLUSIVE	Is inclusive mail	BINARY	
EMAIL	EMAIL_RECIPIENT_DOMAIN_NAMES	Email domain names of recipients	TEXT	6.5.0.23
EMAIL	EMAIL_SENDER_DOMAIN_NAME	Email domain name of sender	TEXT	6.5.0.23
EMAIL	EMAIL_TO_DOMAIN_NAME	Email domain names of email addresses in TO field	TEXT	7.2.0.0
EMAIL	EMAIL_CC_DOMAIN_NAME	Email domain names of email addresses in CC field	TEXT	7.2.0.0
EMAIL	EMAIL_BCC_DOMAIN_NAME	Email domain names of email addresses in BCC field	TEXT	7.2.0.0
EDOC	EDOC_AUTHOR	Populated with file metadata "author".	TEXT	
EDOC	EDOC_CATEGORY	Populated with file metadata "category".	TEXT	
EDOC	EDOC_CHARACTER_COUNT	Populated with number of characters in the document.	NUMERIC	These fields are populated with the metadata captured from the documents. These values are not computed by Venio.
EDOC	EDOC_COMMENTS	Populated with file metadata "comments".	TEXT	
EDOC	EDOC_COMPANY	Populated with file metadata "company".	TEXT	

EDOC	EDOC_CREATED_DATE	Populated with date from "EDOC_CREATED_DATE_TIME" field	DATE	
EDOC	EDOC_CREATED_DATE_TIME	Populated with file metadata "created date/time"	DATE/TIME	
EDOC	EDOC_CREATED_TIME	Populated with time from "EDOC_CREATED_DATE_TIME" field	TIME	
EDOC	EDOC_CREATING_APPLICATION	Populated with file metadata "creating application".	TEXT	
EDOC	EDOC_HAS_COMMENTS	Populated with YES/NO if document has comment metadata.	BINARY	
EDOC	EDOC_HAS_DELETED_TRACK_CHANGE	Populated with YES/NO if document has deleted track changes.	BINARY	
EDOC	EDOC_HAS_HIDDEN_COLUMN	Populated with YES/NO if document has hidden column.	BINARY	
EDOC	EDOC_HAS_HIDDEN_ROW	Populated with YES/NO if document has hidden row.	BINARY	
EDOC	EDOC_HAS_HIDDEN_SHEET	Populated with YES/NO if document has excel hidden sheet.	BINARY	
EDOC	EDOC_HAS_HIDDEN_SLIDE	Populated with YES/NO if document has hidden powerpoint slide.	BINARY	
EDOC	EDOC_HAS_HIDDEN_TEXT	Populated with YES/NO if document has hidden text.	BINARY	
EDOC	EDOC_HAS_MACROS_AND_CODE	Populated with YES/NO if the document contains macro content.	BINARY	
EDOC	EDOC_HAS_REVISIONS	Populated with YES/NO if document has revision number.	BINARY	If revision number is 0 or empty, it will have NO value.
EDOC	EDOC_HAS_SPEAKER_NOTE	Populated with YES/NO if the powerpoint document has speaker note.	BINARY	
EDOC	EDOC_HAS_TRACK_CHANGE_ADDED	Populated with YES/NO if document has added track changes	BINARY	
EDOC	EDOC_HAS_TRACK_CHANGES	Populated with YES/NO if document has track changes (added or deleted).	BINARY	
EDOC	EDOC_KEYWORDS	Populated with file metadata "keywords".	TEXT	
EDOC	EDOC_LAST_AUTHOR	Populated with file metadata "last author".	TEXT	
EDOC	EDOC_LAST_MODIFIED_DATE	Populated with date from "EDOC_LAST_MODIFIED_DATE_TIME" field	DATE	
EDOC	EDOC_LAST_MODIFIED_DATE_TIME	Populated with file metadata "last modified date/time"	DATE/TIME	
EDOC	EDOC_LAST_MODIFIED_TIME	Populated with time from "EDOC_LAST_MODIFIED_DATE_TIME" field	TIME	
EDOC	EDOC_LAST_PRINTED_DATE	Populated with date from "EDOC_LAST_PRINTED_DATE_TIME" field	DATE	
EDOC	EDOC_LAST_PRINTED_DATE_TIME	Populated with file metadata "last printed date/time"	DATE/TIME	

EDOC	EDOC_LAST_PRINTED_TIME	Populated with time from "EDOC_LAST_PRINTED_DATE_TIME" field	TIME	
EDOC	EDOC_LINE_COUNT	Populated with number of lines in the document.	NUMERIC	These fields are populated with the metadata captured from the documents. These values are not computed by Venio.
EDOC	EDOC_PAGE_COUNT	Populated with number of pages in the document.	NUMERIC	These fields are populated with the metadata captured from the documents. These values are not computed by Venio.
EDOC	EDOC_PARAGRAPH_COUNT	Populated with number of paragraphs in the document.	NUMERIC	These fields are populated with the metadata captured from the documents. These values are not computed by Venio.
EDOC	EDOC_PICTURE_TAKEN_LOCATION	Picture Taken Location	TEXT	
EDOC	EDOC_REVISION_NUMBER	Populated with file metadata "revision number"	TEXT	
EDOC	EDOC_SUBJECT	Populated with file metadata "subject"	TEXT	
EDOC	EDOC_TITLE	Populated with file metadata "title".	TEXT	
EDOC	EDOC_WORD_COUNT	Populated with number of words in the document.	NUMERIC	These fields are populated with the metadata captured from the documents. These values are not computed by Venio.
EDOC	EDOC_HAS_HEADERS_FOOTERS	Populated with YES/NO values based on document has header or footer	BINARY	6.5.0.23
EXPORT	EXPORT_FULLTEXT_PATH	Populated with fulltext file folder path of the export.	TEXT	
EXPORT	EXPORT_NAME	Populated with name of export.	TEXT	This is same for all documents for current export.
EXPORT	EXPORT_NATIVE_FILE_NAME	Populated with export native file name.	TEXT	
EXPORT	EXPORT_NATIVE_PATH	Populated with native file folder path of the export.	TEXT	
EXPORT	IS_INCLUDE_EMAIL_THREAD	Populated with YES/NO whether this document is included in export for being part of email thread.	BINARY	
EXPORT	IS_NATIVE_MISSING	Populated with YES/NO if native was not exported due to exceptions.	BINARY	
EXPORT	VOLUME_NAME	Volume name of export	TEXT	
IMAGE	ATTACHMENT_BATES_RANGE	Populated with "BEGIN_BATES" of first attachment & "END_BATES" of last attachment in family set separated by '-' to only parent document.	TEXT	
IMAGE	ATTACHMENT_BATES_RANGE_ALL	Populated with "BEGIN_BATES" of first attachment & "END_BATES" of last attachment in family set separated by '-' to whole family.	TEXT	

IMAGE	BEGIN_ATTACHMENT_BATES	Populated with "BEGIN_BATES" of first child document to only parent document.	TEXT	
IMAGE	BEGIN_ATTACHMENT_BATES_ALL	Populated with "BEGIN_BATES" of first child document to whole family.	TEXT	
IMAGE	BEGIN_BATES	Populated with assigned bates number of 1st page of image of the document	TEXT	
IMAGE	BEGIN_FAMILY_BATES_ALL	Populated with "BEGIN_BATES" of parent document to whole family.	TEXT	
IMAGE	END_ATTACHMENT_BATES	Populated with "END_BATES" of last document to only parent document.	TEXT	
IMAGE	END_ATTACHMENT_BATES_ALL	Populated with "END_BATES" of last document to whole family.	TEXT	
IMAGE	END_BATES	Populated with assigned bates number of last page of image of the document	TEXT	
IMAGE	END_FAMILY_BATES_ALL	Populated with "END_BATES" of last document to whole family.	TEXT	
IMAGE	FAMILY_BATES_RANGE_ALL	Populated with "BEGIN_BATES" of first document & "END_BATES" of last document in family set separated by '-' to whole family.	TEXT	
IMAGE	HAS_REDACTION	Populated with YES/NO values based on redactions applied in any tiff images of a document.	BINARY	
IMAGE	HAS_SLIPSHEET	Populated with YES/NO if image document is placeholder or is slipsheet	BINARY	
IMAGE	IMAGE_PAGE_COUNT	Number of pages of image.	NUMERIC	
WORK PRODUCT	DOCUMENT_NOTES	Populated from user comment made on a document from review module.(default delimiter=;)	MULTI VALUED	Eg: Username:<Username>,Comment:<Comment_value>;
WORK PRODUCT	QC_NOTES	Populated from user note added on a document from QC module.(default delimiter=;)	MULTI VALUED	
WORK PRODUCT	SEARCH_HIT_TERMS	Populate with search expressions of selected saved search	TEXT	
WORK PRODUCT	TAG_COMMENTS	Populated with user comments from applied tag.	MULTI VALUED	For each tag applied, it contains tag name and its tag comment. e.g. Privileged:test comment 1;Confidential:test comment 2
WORK PRODUCT	TAG_NAMES	Populated with applied tag names.	MULTI VALUED	Each tag can be exported as individual field (configurable during export setup)

2 New Field – Log

Field Group	Field Name	Description	Data Type	Version
COMMON	FILE_PASSWORD	Populated of 'Password' of file identified by Venio based on password bank in the project	TEXT	6.5.0.12

COMMON	HASH_VALUE_SECONDARY	Populated with secondary hash value (MD5 or SHA1 based on project setting) of the document	TEXT	6.5.0.12
COMMON	IS_DECRYPTED_FILE	Populated with YES/NO if the document was decrypted by Venio based on password bank in the project	BINARY	6.5.0.12
COMMON	TIMEZONE	Populated with selected timezone for the project	TEXT	6.5.0.12
COMMON	DUPLICATE_CUSTODIAN_NAMES_ALL	Populated with all custodian names which contain duplicates of this document. Applicable for both parent & child documents (default delimiter=;)	MULTI VAUED TEXT	6.5.0.12
EDOC	EDOC_HAS_MACROS_AND_CODE	Populated with YES/NO if the document has macro	BINARY	6.5.0.12
EMAIL	EMAIL_IS_UNREAD	Populated with YES/NO if email was unread	BINARY	6.5.0.12
IMAGE	IMAGE_PAGE_COUNT	Populated with number of (TIFF) images generated by Venio	NUMERIC	6.5.0.12
EDOC	IS_WRITE_PROTECTED	Populated with YES/NO if the document is identified as write protected.	BINARY	6.5.0.12
COMMON	TIMEZONE_OFFSET	Populated with timezone offset i.e. numeric value	NUMERIC	6.5.0.12
COMMON	IS_INCLUSIVE	Populated with Inclusive flag	BINARY	6.5.0.12
COMMON	BEGIN_ATTACHMENT_CONTROL_NUMBER	For parent documents, This field is populated with the "CONTROL_NUMBER" of 1st attachment in its family set.(If there are no attachment or if this document is not the parent, then this field will empty.)	TEXT	6.5.0.12
COMMON	ATTACHMENT_COUNT_PRODUCED	Populated with number of child documents of a family in export. Populated only for parent document.	TEXT	6.5.0.12
COMMON	ATTACHMENT_FILE_NAMES_PRODUCED	Populated with "FILE_NAMES" field of all child documents of a family in export. Populated only for parent document.	MULTI VAUED TEXT	6.5.0.12
IMAGE	HAS_SLIPSHEET	Populated with YES/NO if image document is placeholder or is slipsheet	BINARY	6.5.0.12
COMMON	SEARCH_HIT_TERMS	Populate with search expressions of selected saved search	TEXT	6.5.0.12
EMAIL	EMAIL_DOMAIN_NAMES	Populated with domain names of sender and recipients	TEXT	6.5.0.12
COMMON	TIMEZONE_WINDOWS_FORMAT	Time zone in windows display format	TEXT	6.5.0.12
COMMON	DETECTED_LANGUAGE_ALL	Populated with all identified language of the document.	TEXT	6.5.0.12
IMAGE	HAS_REDACTION	Populated with YES/NO values based on redactions applied in any tiff images of a document.	BINARY	6.5.0.13
COMMON	DUPLICATE_FILE_PATH	Populated with relative file path of all duplicates of this document. Applicable for only parent documents. For children documents, it will be empty.(default delimiter=;)	TEXT	6.5.0.23
COMMON	DUPLICATE_FILE_PATH_ALL	Populated with relative file path of all duplicates of parent file for all document in family(default delimiter=;)	TEXT	6.5.0.23
EDOC	EDOC_HAS_HEADERS_FOOTERS	Populated with YES/NO values based on document has header or footer	BINARY	6.5.0.23
EDOC	HAS_TYPE3_FONT	Flag for pdf files containing type3 fonts	BIT	7.24.0.0

EMAIL	EMAIL_RECIPIENT_DOMAIN_NAMES	Email domain names of recipients	TEXT	6.5.0.23
EMAIL	EMAIL_SENDER_DOMAIN_NAME	Email domain name of sender	TEXT	6.5.0.23
COMMON	GROUP_HASH_VALUE	Populated using hash value of all the documents in the family set	TEXT	6.5.0.26
COMMON	TIMEZONE_OFFSET_WITHOUT_DS	populate the timezone value without daylight saving		
IMAGE	IS_DOC_BAD	Populated with YES/NO to indicate if the tiff of document is bad.	BIT	7.15.0.0
IMAGE	IS_DOC_GOOD	Populated with YES/NO to indicate if the tiff of document is good.	BIT	7.15.0.0
COMMON	IS_EDOC_FILE	Populated with YES/NO to indicate if document is classified as an edoc or not.	BIT	7.15.0.0
IMAGE	BATES_NUMBER	Unique sequential value generated for each tiff image based on prefix, padding and start number provided in export setting (per project).	NVARCHAR	7.15.0.0
COMMON	IS_EMAIL_FILE	Populated with YES/NO to indicate if document is classified as an email or not.	BIT	7.15.0.0
COMMON	IS_CUTOFF_FIXED	Populated with YES/NO to indicate if the cutoff is fixed or not.		
COMMON	IS_ARCHIVE_FILE	Populated with YES/NO to indicate if the document is archived or not.	BIT	7.15.0.0
COMMON	IS_UNKNOWN_FILE	Populated with YES/NO to indicate if the document is classified as unknown or not.	BIT	7.15.0.0
IMAGE	SYSTEM_BATES_NUMBER	Bates number generated when tiff images are created.	NVARCHAR	7.15.0.0
IMAGE	TIFF_MACHINE	Machine name on which tiff is performed.	NVARCHAR	7.15.0.0
IMAGE	TIFF_LOCATION	Location of tiff.	NVARCHAR	7.15.0.0
IMAGE	TIFF_COMPLETED	TIFF STATUS.	NVARCHAR	7.15.0.0
IMAGE	MANUAL_TIFF_NOTE	Manual tiff status.	NVARCHAR	7.15.0.0
COMMON	METADATA_EXTRACTION_SAFEERROR	Metadata Extraction Safeerror		
COMMON	NEAR_DUPLICATE_GROUP_CONTROL_NUMBER	Near Duplicate Group Control Number		
COMMON	NEAR_DUPLICATE_GROUP	Near Duplicate Group Internal File Id		

	P_INTERNAL_FILE_ID			
COMMON	NEAR_DUPLICATE_SIMILARITY_PERCENTAGE	Near Duplicate Similarity Percentage		
COMMON	Priv_From	Priv From		
COMMON	Priv_Title	Priv Title		
COMMON	Priv_To	Priv To		
COMMON	Priv_Type	Priv Type		
WORK PRODUCT	PROMOTED_SOURCE_FILEID	Promoted Source Fileid		
WORK PRODUCT	PROMOTED_SOURCE_PROJECT_ID	Promoted Source Project ID		
WORK PRODUCT	PROMOTED_SOURCE_PROJECT_NAME	Promoted Source Project Name		
COMMON	RELATIVE_FILE_PATH	Relative File Path		
IMAGE	TIFF_COMPLETED	Tiff Completed		
IMAGE	TIFF_LOCATION	TIFF_Location		
Image	TIFF_MACHINE	Tiff Machine_		
IMAGE	TIFF_TYPE	Type of tiff.	NVARCHAR	7.15.0.0
EMAIL	TEAM	Team		
IMAGE	IMAGING_ENGINE_USED	Type of tiff engine used during tiffing.	VARCHAR	7.15.0.0
COMMON	IS_CENTROID_NDD	Populated with YES/NO to indicate if document is Centroid NDD or not.		
IMAGE	IS_NATIVE_INACCESSIBLE	Populated with YES/NO to indicate if document is inaccessible when generating tiff.	BIT	7.15.0.0
IMAGE	IS_TIFF_FAILED	Populated with YES/NO to indicate if failed to generate tiff.	BIT	7.15.0.0
IMAGE	IS_TIME_OUT	Populated with YES/NO to indicate if timed out when generating tiff.	BIT	7.15.0.0
IMAGE	IS_UNABLE_TO_OPENNATIVE	Populated with YES/NO to indicate if unable to open native when generating tiff.	BIT	7.15.0.0
COMMON	RELATIVE_FILE_PATH	Populated with relative file path of the document.	NVARCHAR	7.15.0.0
IMAGE	IMAGING_ENGINE_CONFIGURED	Type of tiff engine configured.	VARCHAR	7.15.0.0
COMMON	EXTRACTED_TEXT_LENGT	Text length of extracted fulltext.	BIGINT	7.15.0.0

	H			
COMMON	FAMILY_COUNT	Number of files in parent-child family.	INT	7.15.0.0
COMMON	DOCUMENT_FAMILY	Document is standalone parent only.	BIT	7.15.0.0
COMMON	REDACTION_REASON	Populated with name of redaction reason	NVARCHAR R	7.24.0.0
COMMON	REDACTION_SET	Populated with name of redaction set	NVARCHAR R	7.24.0.0

3 Renamed Field – Log

Old Field Group	New Field Group	Old Field Name	New Field Name	Description	Data Type	Change
COMMON	COMMON	BEGDOC	BEGIN_CONTROL_NUMBER	Unique sequential value generated for each document based on prefix, padding & start number provided in export setting (per project).	TEXT	FieldName renamed
COMMON	COMMON	ENDDOC	END_CONTROL_NUMBER	Unique sequential value generated for each document based on prefix, padding & start number provided in export setting (per project).	TEXT	FieldName renamed
COMMON	COMMON	ISATTACHMENT	IS_EMAIL_ATTACHMENT	Populated YES/NO whether document is an email attachment.	BINARY	FieldName renamed
COMMON	COMMON	ISEMBEDDED	IS_EDOC_EMBEDDED_FILE	Populated YES/NO If document is an edoc embedded object.	BINARY	FieldName renamed
EMAIL	EMAIL	EMAIL_MEETING_START_DATETIME	EMAIL_START_DATE_TIME	Populated with appointment/task starting date and time	DATE/TIME	FieldName renamed
EMAIL	EMAIL	STARTDATE	EMAIL_START_DATE	Populated with date from 'EMAIL_START_DATE_TIME' field	DATE	FieldName renamed
EMAIL	EMAIL	STARTTIME	EMAIL_START_TIME	Populated with time from 'EMAIL_START_DATE_TIME' field	TIME	FieldName renamed
EMAIL	EMAIL	EMAIL_MEETING_END_DATETIME	EMAIL_END_DATE_TIME	Populated with appointment/task ending date and time	DATE/TIME	FieldName renamed
EMAIL	EMAIL	ENDDATE	EMAIL_END_DATE	Populated with date from 'EMAIL_END_DATE_TIME' field	DATE	FieldName renamed
EMAIL	EMAIL	ENDTIME	EMAIL_END_TIME	Populated with time from	TIME	FieldName

				'EMAIL_END_DATE_TIME' field		me renamed
EMAIL	EMAIL	UNREAD	EMAIL_IS_UNREAD	Populated with YES/NO if email was unread	BINARY	FieldName renamed
EDOC	EDOC	HASMACROSA NDCODE	EDOC_HAS_MACROSA_ AND_CODE	Populated with YES/NO if the document has macro	BINARY	FieldName renamed

4 Removed Field – Log

Field Group	Field Name	Remark
COMMON	EXPORTPATHTIFF	This field is always empty
COMMON	EXPORTPATHREDACTEDTIF	This field is always empty
COMMON	DOCUMENTTYPE	There is another similar field 'Record_type' which is renamed to 'DOCUMENT_TYPE' in 5.3
EMAIL	EMAILREPLIEDDATE	This field is not extracted
EMAIL	EMAILREPLIEDTIME	This field is not extracted
EMAIL	EMAILREPLIEDTO	This field is not extracted
EMAIL	EMAIL_REPLIED_DATETIME	This field is not extracted